

Product code: 470253

DOMEMUL AA 9670

APEO-free Acrylic Emulsion

Specification:

Property	Range	Method / According to standard
Non-volatile matter	39 - 41%	MH1155 / ISO 3251
Viscosity, 23 °C	100 - 800 mPa·s	MH1007 / ISO 3219
pH	7.5 - 9.5	MH1040 / ISO 976

Typical properties:

Property	Value
Solvent	Water
Appearance	Brownish
Density	1.1 kg/L
MFFT	0 °C

Applications:

- » Used for industrial waterborne wood coatings, interior and exterior.
- » Recommended for furniture, joinery and decorative application with non-yellowing, good wetting good water-resistance, low-foaming, flow, transparency and good blocking resistance.

Storage:

The resin should be stored indoors in its original, unopened and undamaged container in a dry place at storage temperatures between 5 °C and 35 °C, for up to 6 months. Protect from freezing and avoid direct sunlight.

Disclaimer

This data is based on experience, for its completeness, we assume no liability. As we take no influence on the processing, it lies within the obligation of the customer to test, whether it is suitable for the intended purpose, before using the product. Any change in the processing procedure, the environmental conditions or the failure to comply with instructions may unfavorably influence the result. This Technical Datasheet is available on our website at www.helios.si. Should there be any discrepancies between this document and the version that appears on the website, then the version on the Website will take precedence.

TECHNICAL DATASHEET

Copyright © Helios Resins & Atcoat | www.resinshelios.com | www.atcoat.com

Issue Date: February 2025

Page: 1/1