

Product code: 402629

## DOMOPUR 0215 35 Wa

### Self-crosslinking Aliphatic Polyurethane Dispersion

#### Specification:

Property	Range	Method / According to standard
Non-volatile matter	34 - 36 %	MH1155 / ISO 3251
Viscosity, 25°C	20 - 100 mPa·s	MH1007 / ISO 3219
pH	7.0 - 8.5	MH1040 / ISO 976

#### Typical properties:

Property	Value
Appearance	Light yellow, slightly hazy liquid
Density	1.05 kg/L
Neutralisation agent	0.9% triethylamine, as salt
Free monomer	max. 1000 ppm

#### Remarks:

Non yellowing, high abrasion, chemical, black heel mark, and scratch resistance.

#### Applications:

1K and 2K finishes for parquet, concrete, cork, and PVC flooring.

#### Storage:

The resin should be stored indoors in its original, unopened and undamaged container in a dry place at storage temperatures between 5 °C and 35 °C, for up to 6 months. Protect from freezing and avoid exposure to direct sunlight.

#### Disclaimer

This data is based on experience, for its completeness, we assume no liability. As we take no influence on the processing, it lies within the obligation of the customer to test, whether it is suitable for the intended purpose, before using the product. Any change in the processing procedure, the environmental conditions or the failure to comply with instructions may unfavorably influence the result. This Technical Datasheet is available on our website at [www.helios.si](http://www.helios.si). Should there be any discrepancies between this document and the version that appears on the website, then the version on the Website will take precedence.